



For contract construction projects

W20-1(0)-48

For maintenance and utility projects

W21-4(0)-48

W20-4(0)-48

W20-7a(0)-48

or

W20-1101(0)-48

W20-4(0)-48

W20-7a(0)-48

or

W20-1101(0)-48

GENERAL NOTES

This Standard is used where at any time, any vehicle, equipment, workers or their activities will encroach on the pavement during widening operations.

* Minimum distance is 60 m (200'). Maximum distance to be determined by the Engineer but in no case to exceed the length of 1/2 day's normal operation.

** Signs are not required if distance between work operations is less than 600 m (2000') unless restricted sight distance exists.

Two flaggers are required for each separate operation.

All dimensions are in millimeters (inches) unless otherwise shown.

SYMBOLS

- Work area
- Active Work area
- Sign
- Barricade, drum, or vertical panels
- Flagger with traffic control sign

Illinois Department of Transportation	
APPROVED January 1, 1999	ISSUED 1-1-97
ENGINEER OF OPERATIONS	
APPROVED January 1, 1999	
ENGINEER OF DESIGN AND ENVIRONMENT	

DATE	REVISIONS
1-1-99	Rev. RCA sign spacing.
1-1-97	Renum. Standard 2311-12.
	Deleted orange flags.
	Rev. w areas. Added GN.

LANE CLOSURE 2L, 2W
PAVEMENT WIDENING
FOR SPEEDS \geq 45 MPH

STANDARD 701326-01